

TRANSMITTAL LETTER TO THE UNITED STATES
DESIGNATED/ELECTED OFFICE (DO/EO/US)
CONCERNING A FILING UNDER 35 U.S.C. 371

Attorney Docket No. 02039

U.S. Application No. (if known,
see 37 CFR 1.55)

10/049618

INTERNATIONAL APPLICATION NO.
PCT/EP00/08204INTERNATIONAL FILING DATE
August 23, 2000PRIORITY DATE CLAIMED
August 26, 1999

TITLE OF INVENTION

DEVICE FOR DRESSING, IN PARTICULAR SHAPENING, A TOOL HAVING A PLURALITY OF TEETH

APPLICANT(S) FOR DO/EO/US

Reinhold Reiling, Karl Reiling

Applicant herewith submits to the United States Designated Office (DO/EO/US) the following items and other information:

1. ☒ This is a **FIRST** submission of items concerning a filing under 35 U.S.C. 371.
2. ☐ This is a **SECOND** or **SUBSEQUENT** submission of items concerning a filing under 35 U.S.C. 371.
3. ☐ This is an express request to begin national examination procedures (35 U.S.C. 371(f)) at any time rather than delay examination until the expiration of the applicable time limit set in 35 U.S.C. 371(b) and PCT Articles 22 and 39(1).
4. ☐ A proper Demand for International Preliminary Examination was made by the 19th month from the earliest claimed priority date.
5. ☒ A copy of the International Application as filed (35 U.S.C. 371(c)(2))
 - a. ☐ is transmitted herewith (required only if not transmitted by the International Bureau).
 - b. ☒ has been transmitted by the International Bureau.
 - c. ☐ is not required, as the application was filed in the United States Receiving Office (RO/US).
6. ☒ A translation of the International Application into English (35 U.S.C. 371(c)(2)).
7. ☐ Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371(c)(3)).
 - a. ☐ are transmitted herewith (only if not required by the International Bureau).
 - b. ☐ have been transmitted by the International Bureau.
 - c. ☐ have not been made; however, the time limit for making such amendments has NOT expired.
 - d. ☐ have not been made and will not be made.
8. ☐ A translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)).
9. ☒ An oath or declaration of the inventor(s) (35 U.S.C. 371(c)(4)).
10. ☐ A translation of the annexes to the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371(c)(5)).

Items 11 to 16 below concern document(s) or information included:

11. ☐ An Information Disclosure Statement under 37 CFR 1.97 and 1.98.
12. ☐ As assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included.
13. ☒ A **FIRST** preliminary amendment.
14. ☐ A **SECOND** or **SUBSEQUENT** preliminary amendment.
15. ☐ A substitute specification.
16. ☐ A change of power of attorney and/or address letter.
17. ☐ Other items or information:


10/049618

JC13 Rec'd PCT/PTO 22 FEB 2002

17. <input checked="" type="checkbox"/> The following fees are submitted:				CALCULATIONS PTO USE ONLY	
BASIC NATIONAL FEE (37 CFR 1.492 (a)(1)-(5):					
Neither international preliminary examination fee (37 CFR 1.482)					
Nor international search fee (37 CFR 1.445(a)(2) paid to USPTO					
And International Search Report not prepared by EPO or JPO..... \$1,040.00					
International preliminary examination fee (37 CFR 1.482) not paid to USPTO but International Search Report prepared by EPO or JPO.....\$890.00					
International preliminary examination fee (37 CFR 1.482) not paid to USPTO but International search fee (37 CFR 1.445(a)(2)) paid to USPTO..... \$740.00					
International preliminary examination fee paid to USPTO (37 CFR 1.482) But all claims did not satisfy provisions of PCT Article 33(1)-(4).....\$710.00					
International preliminary examination fee paid to USPTO (37 CFR 1.482) And all claims satisfied provisions of PCT Article 33(1)-(4)..... \$100.00					
ENTER APPROPRIATE BASIC FEE AMOUNT =				\$890.00	
Surcharge of \$130.00 for furnishing oath or declaration later than <input type="checkbox"/> 20 <input checked="" type="checkbox"/> 30 months from the earliest claimed priority date (37 CFR 1.492(e).				\$	
CLAIMS	NUMBER FILED	NUMBER EXTRA	RATE		
Total Claims	20 -20=		X \$18.00	\$	
Independent Claims	1 -3=		X \$84.00	\$	
MULTIPLE DEPENDENT CLAIM(S) (if applicable)				\$	
TOTAL OF ABOVE CALCULATIONS =				\$890.00	
Reduction of 1/2 for filing by small entity, if applicable. A Small Entity Statement must also be filed (Note 37 CFR 1.9, 1.27, 1.28).				\$445.00	
SUBTOTAL =				\$445.00	
Processing fee of \$130.00 for furnishing English translation later than <input type="checkbox"/> 20 <input type="checkbox"/> 30 months from the earliest claimed priority date (37 CFR 1.492(f).				\$	
TOTAL NATIONAL FEE =				\$445.00	
Fee for recording the enclosed assignment (37 CFR 1.21(h)). The assignment must be accompanied by an appropriate cover sheet (37 CFR 3.28, 3.31).				\$	
TOTAL FEES ENCLOSED =				\$445.00	
				Amount to be refunded:	\$
				charged:	\$

- a. ☒ A check in the amount of \$445.00 to cover the above fees is enclosed.
- b. ☐ Please charge my Deposit Account No. 04-0753 in the amount of \$ _____ to cover the above fees. A duplicate copy of this sheet is enclosed.
- c. ☒ The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any overpayment to Deposit Account No. 04-0753. A duplicate copy of this sheet is enclosed.
- d. ☐ A payment of \$ _____ is made by credit card. A Credit Card Payment Form (PTO-2038) is attached hereto. The Commissioner is hereby authorized to charge payment of any additional filing fees required under 37 CFR 1.16 or any patent application processing fees under 37 CFR 1.17, or credit any over payment to the credit card account shown on the attached Credit Card Payment Form. Refund of all amounts overpaid, including those of twenty-five dollars or less, is specifically requested. Any fees not accepted by the credit card shown on Form PTO-2038 may be charged to Deposit Account No. 04-0753.

SEND ALL CORRESPONDENCE TO:
 BREZINA & EHRLICH
 47 West Polk Street
 Suite 333
 Chicago, IL 60605
 Tel. (312) 408-0077
 Fax (312) 408-0044



SIGNATURE

Ira J. Schultz

NAME

28666

REGISTRATION NUMBER

Dkt. 02039

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re the Application of: Group Art Unit:
REINHOLD REILING et al Examiner:

Serial No.: US National Phase of
PCT/EP00/08204

Filed: concurrently herewith

For: DEVICE FOR DRESSING, IN PARTICULAR SHARPENING,
A TOOL HAVING A PLURALITY OF TEETH

PRELIMINARY AMENDMENT

Honorable Assistant Commissioner for Patents
Washington, DC 20231

Sir:

Before calculation of the filing fee, please amend the
above-identified application as follows:

IN THE CLAIMS:

Please amend the claims as set forth hereinbelow and in
the attached appendix:

4. (Amended) The device according claim 1, wherein at
least one of said guiding elements is extending substantially
over the entire length of said support surface.

5. (Amended) The device according to claim 1, wherein at
least one of said guiding elements is designed as an elongated
slot or an opening in said support surface.

10049618-1000

7. (Amended) The device according to claim 1, wherein at least one of said elongated slots acting as guiding element is of a linear or of a curved design.

8. (Amended) The device according to claim 1, wherein at least one of said elongated slots acting as guiding elements is positioned substantially parallel to the longitudinal direction of said support surface.

9. (Amended) The device according to claim 1, wherein at least one of said elongated slots acting as guiding elements is positioned inclined to the longitudinal direction of said support surface.

10. (Amended) The device according to claim 1, comprising a mounting device for a pin shaped tool.

11. (Amended) The device according to claim 10, wherein said mounting device is pivotally connected to said device for dressing said tool.

12. (Amended) The device according to claim 10, wherein said mounting device comprises at least two mounting blocks, said mounting blocks defining a space wherein an adapter can be inserted with clearance.

13. (Amended) The device according to claim 10, wherein said adapter having a mounting opening, said mounting opening being capable of receiving said pin shaped tool.

14. (Amended) The device according to claim 12, wherein

said adapter comprises an extension, said extension being inserted into one of said spaces defined by said mounting blocks.

15. (Amended) The device according to claim 12, wherein said adapter additionally comprises a clamping arrangement for securing a pin-shaped tool in said mounting device of said adapter.

17. (Amended) The device according to claim 16, wherein said body of said tightening screw can be inserted in one of said spaces of said mounting device.

18. (Amended) The device according to claim 1, wherein said holding device for said dressing tool comprises a guide rail along which said dressing tool can be moved and can be locked in position by means of said locking element.


19. (Amended) The device according to claim 1, wherein said holding device additionally comprises a ball end bearing said dressing tool and enabling said dressing tool to be tilted.

20. (Amended) The device according to claim 1, wherein said holding device possesses an adjustment means for positioning said dressing tool.

REMARKS

The claims have been amended to delete all multiple dependencies.

Respectfully submitted,
John C. Brezina, Esq., by



Ira J. Schultz
Registration No. 28666
(703)412-1155, ext. 23

BREZINA & EHRLICH
47 West Polk Street
Suite 333
Chicago, IL 60605
(312)408-0077

20220825407

APPENDIX

IN THE CLAIMS:

4. (Amended) The device according [to any one of claims 1 to 3] claim 1, wherein at least one of said guiding elements is extending substantially over the entire length of said support surface.

5. (Amended) The device according to [any one of claims 1 to 4] claim 1, wherein at least one of said guiding elements is designed as an elongated slot or an opening in said support surface.

7. (Amended) The device according to [any one of claims 1 to 6] claim 1, wherein at least one of said elongated slots acting as guiding element is of a linear or of a curved design.

8. (Amended) The device according to [any one of claims 1 to 7] claim 1, wherein at least one of said elongated slots acting as guiding elements is positioned substantially parallel to the longitudinal direction of said support surface.

9. (Amended) The device according to [any one of claims 1 to 8] claim 1, wherein at least one of said elongated slots acting as guiding elements is positioned inclined to the longitudinal direction of said support surface.

10. (Amended) The device according to [any one of claims

1 to 9] claim 1, comprising a mounting device for a pin shaped tool.

11. (Amended) The device according to [any one of claims 1 to 10] claim 10, wherein said mounting device is pivotally connected to said device for dressing said tool.

12. (Amended) The device according to [any one of claims 1 to 11] claim 10, wherein said mounting device comprises at least two mounting blocks, said mounting blocks defining a space wherein an adapter can be inserted with clearance.

13. (Amended) The device according to [any one of claim 1 to 12] claim 10, wherein said adapter having a mounting opening, said mounting opening being capable of receiving said pin shaped tool.

14. (Amended) The device according to [any one of claim 1 to 13] claim 12, wherein said adapter comprises an extension, said extension being inserted into one of said spaces defined by said mounting blocks.

15. (Amended) The device according to [any one of claims 1 to 14] claim 12, wherein said adapter additionally comprises a clamping arrangement for securing a pin-shaped tool in said mounting device of said adapter.

17. (Amended) The device according to [any one of claims 1 to 16] claim 16, wherein said body of said tightening screw can be inserted in one of said spaces of said mounting device.

18. (Amended) The device according to [any one of claims 1 to 17] claim 1, wherein said holding device for said dressing tool comprises a guide rail along which said dressing tool can be moved and can be locked in position by means of said locking element.

19. (Amended) The device according to [any one of claims 1 to 18] claim 1, wherein said holding device additionally comprises a ball end bearing said dressing tool and enabling said dressing tool to be tilted.

20. (Amended) The device according to [any one of claims 1 to 19] claim 1, wherein said holding device possesses an adjustment means for positioning said dressing tool.

i2/prt

TITLE OF THE INVENTION

DEVICE FOR DRESSING, IN PARTICULAR SHARPENING, A TOOL
HAVING A PLURALITY OF TEETH

5 FIELD OF THE INVENTION

The present invention relates to a device for tool dressing. More specifically, the present invention relates to a device for sharpening a tool having a plurality of teeth.

BACKGROUND OF THE INVENTION

10 It is important for handymen to be able to dress, more specifically, to be able to sharpen, in a simple and convenient way, the tools that have become dull due to long and constant use. The common difficulty arising in such instance is that the tool, in particular a saw blade and/or a drill, has to be kept firmly in position during the sharpening so as to maintain the pertinent surfaces of the tool to be dressed in a defined position, so as to be easily dressed by a sharpening tool without endangering the user.

15 From US Patent 3,427,903 (further referred to as '903) a device for dressing a sawing tool having a plurality of sawing teeth is known. The device is described as having a support surface possessing a dressing side, on which the sawing tool can be placed. The support surface comprises guiding elements that run orthogonally to the dressing side and in which adjustable positioning elements are arranged. These positioning elements are used to firmly clamp the sawing tool to the support surface, hence immobilizing it to the support surface such that the support surface, itself displaceable by means of a feeding mechanism, can be successively moved past a dressing element of a dressing tool arranged in front of the support surface. The positioning elements act upon the side of the sawing tool opposite the dressing tool.

20 The device described in '903 has the disadvantage that it is not particularly suited for handymen due to its relatively complicated design. Another, more serious disadvantage of the device is that only elongated sawing tools such as for example, the saw blade of a hand saw, in which the teeth of the saw are arranged straightly and linearly, can be dressed.

Another disadvantage of the device described in '903, is that it does not permit sharpening of circular tools such as, for example, circular saw blades or circular milling tools. Indeed, to achieve the dressing of the individual teeth of the sawing tool, the support surface with the sawing tool firmly clamped onto it in a fixed position, has to be moved past the dressing tool by means of the feeding mechanism moving the support surface. Such arrangement does not permit to dress circular tools.

Yet a further disadvantage of the device described in '903 is that due to the arrangement of the dressing tool relative to the support surface, it is only possible to work on saw teeth possessing a triangular tooth contour. It is therefore not possible to sharpen saw teeth having a different configuration such as, for example, saw teeth of a trapezoidal shape. For the same reason it is not possible either to work on the back of saw teeth or on insert teeth.

It is therefore the object of the present invention to further develop a device of the aforementioned type so that the device according to the invention has a simple design and is particularly suited for the dressing of circular tools.

SUMMARY OF THE INVENTION

This object is solved by a device for dressing a tool having a plurality of teeth, wherein said device comprises a support surface having guiding elements, said guiding elements having at least two movable positioning elements, said movable positioning elements being adapted to be locked in a fixed position within said guiding elements such that said positioning elements form a stop for said tool; and a dressing tool mounted in a holding device positioned in front of a dressing side of said support surface, wherein said dressing tool is locked in position by a locking element during the dressing of said teeth, said dressing tool not being movable at least in a direction running substantially parallel to said dressing side; wherein said positioning elements are arranged in said guiding elements in said support surface such that said tool to be dressed engages with said positioning elements at its side turned towards said dressing side of said support surface, so that said tool can be moved towards said positioning elements by a feed movement proceeding in a feed direction

starting from a feed side of the support surface, said feed side being located opposite said dressing side of said support surface, and being directed towards said dressing side; and wherein said engagement between said positioning elements and said tool can be discontinued by a return movement of said tool, said movement being oppositely directed to said feed movement.

The inventive device has the advantage that an easy positioning, especially of circular saw blades, for the sharpening of the sawing teeth of sawing blades, or of other circular tools having at least one tooth, is achieved. According to the invention it is provided that the guiding elements arranged in the support surface (which provides a good support for the tool lying on it) and accomodating the positioning elements being adjustable in different positions in the guiding elements, are arranged in such a way that the tool to be dressed by the inventive device can be moved to the positioning elements engaging the tool in its area adjacent to the dressing side, by means of a feeding movement proceeding in the feeding direction starting from said feed side, which is located opposite said dressing side of said support surface, and being directed toward said dressing side. This measure advantageously achieves that the inventive device can be used for a large number of circular tools having sawing blades with different diameters. Furthermore, the adjustability of the positioning elements in different positions in their guiding elements results in an easy adaptation to various blade diameters.

Additionally, the device according to the present invention does not only distinguish itself by its simple operation but also by its simple design, consequently dispensing with any powered feeding mechanisms for dressing tools. During the dressing operation, the dressing tool is advantageously positioned in a suitable position in front of the tool to be dressed, and remains locked in this position during the entire dressing operation, unless a readjustment is required due to varying tooth contours.

The device according to the present invention advantageously allows for teeth of any contour, particularly the back of teeth or trapezoidally designed teeth or insert teeth to be dressed.

An advantageous further development of the invention provides that the device comprises a drill mounting device for a drilling tool in which the drilling tool to be sharpened can be locked in position. Such a measure has the advantage that with the inventive device not only saw blades but also drilling tools can be dressed, especially for the purpose of sharpening.

A further advantageous development of the invention provides that the device comprises means for assisting in the mounting of a drilling tool in an adapter, which can be inserted in the mounting unit of the device. Such a measure has the advantage that the mounting of the drilling tool in the adapter can be carried out with particular ease.

Yet another further advantageous development of the invention provides that the device comprises a holding device for the dressing tool, with which the dressing of the tool being positioned by the inventive device is to be carried out. Such a measure has the advantage that in an very simple way a defined positional relation between the tool to be dressed and the corresponding dressing tool can be established.

Further advantageous developments of the invention are subject of the dependent claims.

BRIEF DESCRIPTION OF THE DRAWINGS

The present invention will be further understood from the following description with reference to the drawings in which:

Figure 1 illustrates a top view of the device in accordance with a first embodiment of the present invention;

Figure 2 illustrates a top view of the device of Figure 1 together with a saw blade to be dressed;

Figure 3 illustrates a view of the first embodiment along direction III of Figure 1;

Figure 4 illustrates a view of the first embodiment along direction IV of Figure 1;

Figures 5, 5a, 5b and 5c illustrate a representation of a mounting unit of the device of the present invention;

Figure 6 illustrates an embodiment of an adapter for the mounting unit;

Figure 7 illustrates an enlarged representation of a first embodiment of a support

surface;

Figure 8 illustrates an enlarged representation of a second embodiment of the support surface;

Figure 9 illustrates an enlarged representation of a third embodiment of the support surface;

Figure 10 illustrates an enlarged representation of a fourth embodiment of the support surface;

Figure 11 illustrates an enlarged representation of a fifth embodiment of the support surface; and

Figure 12 illustrates an enlarged representation of a sixth embodiment of the support surface.

DESCRIPTION OF PREFERRED EMBODIMENTS

The device for dressing a tool, in particular a saw blade and/or a drilling tool, as shown in Figures 1 to 3 and generally designated by 1, comprises a support surface 10 which is positioned on a suitable carrier structure 9. The support surface 10 has guiding elements 11 which, in the case shown here, are designed as elongated slots 12. Positioning elements 13 are slidably arranged in the guiding elements 11, and which, in the case shown here, are designed as positioning pins 14.

As can be seen best from Figures 2 and 3, device 1 possesses at its front side a holding device 20 for a dressing tool 25, in particular a grinding device with a motor driven grinding wheel 26. The holding device 20 for the dressing tool 25 can be moved along a guide rail 21 of device 1, in the longitudinal direction of the support surface 10, thus substantially parallel to a dressing side 10' of the support surface 10. The holding device 20 can be locked in position by means of a stop lever 21' representing a locking element. The holding device 20 additionally comprises a ball end 22, by which means the dressing tool 25 can be tilted in a way known to those skilled in the art. A fine adjustment device 23 allows, by means of a suitable actuation of an adjustment screw 23', an exact positioning of the dressing tool 25 and thus the grinding wheel 26 representing a dressing element of the dressing tool 25, with respect to the tool's surface to be dressed, for example, the circular saw blade S (see Fig.

2). This particularly allows for an exact control of the thickness of material to be removed by the grinding wheel 26. In order not to obstruct the movement of the grinding wheel 26 of the dressing tool 25, it is preferable that the support surface 10 is provided with a concave recess 17 in its dressing side 10' adjacent to the dressing tool 25.

In order to be able to dress, in particular to be able to sharpen the saw blade S, shown sketched in Figure 2, by means of the dressing tool 25, the saw blade S is positioned flat on the support surface 10. The two positioning pins 14 are moved in their guiding elements 11 until a secure stop is formed for the saw blade S. It can be provided in this case that the positioning pins 14 are arranged in such a way in the guiding elements 11, so that the positioning pins 14 enter at least to some extent into the open spaces defined between two saw teeth S1, S2 and S1', S2', respectively, as is shown, for example, in Figure 2. However, it is also possible to arrange the positioning pins 14 in such a way, so that they engage flanks SF arranged in the circumferential direction of the sawing blade SF.

As can be best seen from Figure 2, it is preferred that the positioning pins 14 are arranged on the support surface 10 in such a manner, so that they act upon the front section of saw blade S facing the dressing side 10' of the support surface 10. This arrangement has the advantage that the saw blade S can be easily positioned in an unobtrusive manner on the support surface 10 of device 1 by the positioning pins 14 and is therefore appropriately positioned for the dressing operation.

When saw blade S has been positioned as previously described, saw tooth S4 is in the dressing range of grinding wheel 26, and is dressed with the grinding wheel 26 of the dressing tool 25. For this purpose, the dressing tool 25 was moved beforehand so far along the guide rail 21 of device 1 and, if required, tilted in such a way around the ball end 22 until the grinding wheel 26 of the dressing tool 25 is aligned in accordance with the dressing operation to be carried out on saw tooth S4. The dressing tool 25 is then locked in this sharpening position by clamping the stop lever 21', which represents a locking element for the sharpening tool 25, as well as, if required, through fixing the ball end 22. This ensures that the dressing tool 25 is in a fixed position during the dressing of saw tooth S4, at least

in the direction of guide rail 21.

After the dressing of saw tooth S4, saw blade S is pulled back slightly against its direction of feed Z, in fact it is sufficiently pulled back such that the active engagement of the positioning pins 14 with the saw blade S is discontinued. The saw blade S can therefore be moved by means of a simple manual rotation in its circumferential direction so that after an appropriate movement of the saw blade S in the direction of feed Z, the two positioning pins 14 enter into the open spaces following the former ones in the direction of rotation, defined between the saw teeth S2, S3 and S2', S3' respectively. Saw tooth S5, which is now in the dressing range of the grinding wheel 26, is subsequently dressed, etc.

Since, usually all saw teeth S1-S5 of a saw blade have the same tooth contour, it is not necessary to change the alignment of the grinding wheel 26. It is understood that with deviating teeth contours of the saw teeth S1-S5, the dressing tool 25 can be realigned as required by an appropriate displacement along the guide rail 21, or by a resetting of the ball end 22.

The aforementioned sharpening operation comprising; advancing the saw blade S in the direction of feed Z starting at a feed side 10", being opposite the dressing side 10' of the support surface 10, until the positioning pins 14 engage with the section of the saw blade S that is facing the dressing side 10', hence forming a stop for the saw blade S; dressing of one of the saw teeth S1-S5; pulling back the saw blade S in a direction opposite the direction of feed Z until the active engagement between saw blade S and the positioning pins 14 is discontinued; rotating the saw blade S until the next to be dressed saw tooth S1-S5 is in front of the dressing tool 25; advancing the saw blade S in the direction of feed until the positioning pins 14 again engage saw blade S; is carried out until all saw teeth S1-S3 of saw blade S are dressed. Finally, saw blade S is removed from device 1 by simply pulling the saw blade S back from the support surface 10.

In order to be able to not only dress, especially sharpen, saw blades or similar, preferably circular objects having on their circumference a contour to be dressed, with the present

device, but also pin shaped objects such as, for example, drill bits or similar drilling tools, the device 1 is preferably provided with a mounting device 40 into which, for example, a drill bit can be inserted.

5 The mounting device 40 can best be seen from Fig. 3 and is shown in greater detail in Figs. 5 and 6. More specifically, Fig. 5a shows a side view, Fig. 5b shows a top view, and Fig. 5c shows another side view of the mounting device 40 from a direction A.

10 The mounting device 40 possesses a number of mounting blocks 41a-41e, which are arranged at a distance from one another such that between two adjacent mounting blocks 41a-41d there is a space 42a-42d. These spaces 42a-42d are dimensioned in such a way so that an extension 51 of an adapter 50 as shown in Fig. 6, can be inserted with clearance.

15 Referring to Fig. 6, the adapter 50 possesses a central element 52 which is provided with a mounting opening 53 for a drill bit. A V-shaped groove 54 facilitates the locking into position of small diameter drill bits in the mounting opening 53.

20 A tightening screw 55, entering the mounting opening 53, serves to secure the drill bit in the mounting opening 53. It is advantageous if the tightening screw 55 is of such a design so that its body 55' can be likewise inserted into one of the spaces 42a-42d of the mounting unit 40, so that it can fulfill the function corresponding to the extension 51.

25 This arrangement advantageously allows one to dress two oppositely located surfaces (180° with respect to one another) of a pin shaped tool, in a single mounting. For the sharpening of the first surface for example, extension 51 is inserted into one of the spaces 42a-42d of the mounting device 40. After completion of the sharpening operation, the adapter 50 is removed from the mounting device 40 and rotated by 180° and then reinserted into the mounting device 40 in such a way so that the body 55' of the tightening screw 55 is inserted into one of the spaces 42a-42d between two mounting
30 blocks 41a-41e.

After the drill bit is clamped in the adapter 50, extension 51 is inserted into one of the spaces

42a-42d of the mounting device 40, so that a front area of the drill bit protrudes from the front area 41a' of the front mounting block 41a. The mounting device 40 is then positioned appropriately with respect to the carrying structure 9 of the device 1 by pivoting it around an axis 43, in which case the mounting device 40 is locked in its final position by means of a clamping element 45, arranged in an elongated slot 44 (Figures 3 and 4).

The ability to pivot the mounting device 40 is particularly advantageous for sharpening four faced drill bits, since in this case the angle of the grinding wheel 26 can be easily adjusted to the angle of the surface to be sharpened. The dressing tool 25 is then aligned correspondingly. By advancing the adapter 50, which is mounted with clearance in one of the spaces 42a-42d, the surface of the drill bit to be dressed is now pressed against the grinding wheel 26.

In order to achieve a correct insertion of the drill bit into the adapter 50, device 1 preferably possesses a means 60 for assisting in the mounting of the drilling tool.

It is assumed in the above description that one positioning element 13 is associated with one linearly running elongated slot 12, which acts as guiding element 11. As the illustration in Figure 8 shows, it is not necessary for the elongated slots 12 to be of a linear design. On the contrary, it is also possible that at least one of the elongated slots 12 of the support surface 10 is of a curved design.

Figure 9 illustrates another embodiment of the support surface 10, in which the elongated slots 12 on the left-hand side are of a linear design and parallel to the longitudinal extension of the support surface 10, whereas the elongated slots 12 on the right-hand side are linear, but arranged in an inclined manner to the longitudinal direction of the support surface 10.

Figures 10 and 11 further illustrate other embodiments of the support surface 10, differing from the aforementioned embodiments in that the elongated slots 12 substantially extend over the entire length of the support surface 10, such that the two positioning pins 14 can be inserted in each one of these elongated slots 12.

Figure 12 illustrates another embodiment of the support surface 10. Instead of the elongated slots 12 of the previously described embodiments, a matrix shaped grid of openings 16 is provided wherein the positioning pins 14 acting as positioning elements 13 can be inserted.

- 5 Although the present invention has been described hereinabove by way of preferred embodiments thereof, it can be modified, without departing from the spirit and nature of the subject invention as defined in the appended claims.

CLAIMS

1. A device for dressing a tool having a plurality of teeth, wherein said device comprises a support surface having guiding elements, said guiding elements having at least two movable positioning elements, said movable positioning elements being adapted to be locked in a fixed position within said guiding elements such that said positioning elements form a stop for said tool to be dressed; and a dressing tool mounted in a holding device positioned in front of a dressing side of said support surface,

wherein said dressing tool is locked in position by a locking element during the dressing of said teeth, hence said dressing tool not being movable at least in a direction running substantially parallel to said dressing side;

wherein said positioning elements are arranged in said guiding elements in said support surface such that said tool to be dressed engages with said positioning elements at its side turned towards said dressing side of said support surface, so that said tool to be dressed can be moved towards said positioning elements by a feed movement proceeding in a feed direction starting from a feed side of the support surface, said feed side being located opposite said dressing side of said support surface, and being directed towards said dressing side; and

wherein said engagement between said positioning elements and said tool to be dressed can be discontinued by a return movement of said tool to be dressed, said movement being oppositely directed to said feed movement.

2. The device according to claim 1, wherein said support surface is designed in such a way and that said positioning elements are arranged in said support surface so that the engagement between said positioning elements and said tool is discontinued by pulling back said tool in said direction opposite said feed movement and said tool to be dressed can be rotated on said support surface of said device, for positioning said tool in its subsequent dressing position.

3. The device according to claim 2, wherein one positioning element is positioned in one guiding element.

4. The device according to any one of claims 1 to 3, wherein at least one of said guiding elements is extending substantially over the entire length of said support surface.

5. The device according to any one of claims 1 to 4, wherein at least one of said guiding elements is designed as an elongated slot or an opening in said support surface.

6. The device according to claim 5, wherein said support surface comprises a matrix-like grid of openings.

7. The device according to any one of claims 1 to 6, wherein at least one of said elongated slots acting as guiding element is of a linear or of a curved design.

8. The device according to any one of claims 1 to 7, wherein at least one of said elongated slots acting as guiding elements is positioned substantially parallel to the longitudinal direction of said support surface.

9. The device according to any one of claims 1 to 8, wherein at least one of said elongated slots acting as guiding elements is positioned inclined to the longitudinal direction of said support surface.

10. The device according to any one of claims 1 to 9, comprising a mounting device for a pin shaped tool.

11. The device according to any one of claims 1 to 10, wherein said mounting device is pivotally connected to said device for dressing said tool.

12. The device according to any one of claims 1 to 11, wherein said mounting device

comprises at least two mounting blocks, said mounting blocks defining a space wherein an adapter can be inserted with clearance.

13. The device according to any one of claim 1 to 12, wherein said adapter having a mounting opening, said mounting opening being capable of receiving said pin shaped tool.

14. The device according to any one of claim 1 to 13, wherein said adapter comprises an extension, said extension being inserted into one of said spaces defined by said mounting blocks.

15. The device according to any one of claims 1 to 14, wherein said adapter additionally comprises a clamping arrangement for securing a pin-shaped tool in said mounting device of said adapter.

16. The device according to claim 15, wherein said clamping arrangement comprises a tightening screw possessing a body.

17. The device according to any one of claims 1 to 16, wherein said body of said tightening screw can be inserted in one of said spaces of said mounting device.

18. The device according to any one of claims 1 to 17, wherein said holding device for said dressing tool comprises a guide rail along which said dressing tool can be moved and can be locked in position by means of said locking element.

19. The device according to any one of claims 1 to 18, wherein said holding device additionally comprises a ball end bearing said dressing tool and enabling said dressing tool to be tilted.


20. The device according to any one of claims 1 to 19, wherein said holding device possesses an adjustment means for positioning said dressing tool.

ABSTRACT

A device for dressing a tool having a plurality of teeth, wherein said device comprises a support surface having guiding elements, said guiding elements having at least two movable positioning elements, said movable positioning elements being adapted to be locked in a fixed position within said guiding elements such that said positioning elements form a stop for said tool; and a dressing tool mounted in a holding device positioned in front of a dressing side of said support surface, wherein said dressing tool is locked in position by a locking element during the dressing of said teeth, hence said dressing tool not being movable at least in a direction running substantially parallel to said dressing side; wherein said positioning elements are arranged in said guiding elements in said support surface such that said tool to be dressed engages with said positioning elements at its side turned towards said dressing side of said support surface, so that said tool can be moved towards said positioning elements by a feed movement proceeding in a feed direction starting from a feed side of the support surface, said feed side being located opposite said dressing side of said support surface, and being directed towards said dressing side; and wherein said engagement between said positioning elements and said tool can be discontinued by a return movement of said tool, said movement being oppositely directed to said feed movement.

(Figure. 1)

202208196400T






Fig.2

202203154001




Fig.3

20220101




Fig.4






Fig. 6






Fig 7

202208164001




Fig. 8




Fig. 9




Fig. 10




Fig. 11

202220" 8T95400T




Fig. 12

DECLARATION AND POWER OF ATTORNEY

FOR APPLICATION TITLED: Device for post-processing, more particularly sharpening, a tool having a plurality of teeth

INVENTOR(S): Reinhold Reiling, Remchinger Strasse 4, D-75203 Königsbach-Stein, Germany; Karl Reiling, Remchinger Strasse 4, D-75203 Königsbach-Stein, Germany

As a below named inventor, I hereby declare that: my residence, post office address and citizenship are stated as below next to my name; that I believe I am an original, first and sole inventor of the subject matter which is claimed and for which a patent is sought on the invention entitled: Device for post-processing, more particularly sharpening, a tool having a plurality of teeth

the specification of which is attached.

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations, Sec. 1.56(a).

I hereby claim foreign priority benefits under Title 35, United States Code, Sec. 119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed (if none, type or write none):

✓ German Patent No. 199 40 635.9,
dated August 26, 1999

I hereby claim the benefits under Title 35, United States Code, Sec. 120 of any United States application(s) listed below and, in so far as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, Sec. 112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, Sec. 1.56(a) which occurred between the filing date of the prior application and the national or PCT

DECLARATION AND POWER OF ATTORNEY

-continued-

international filing date of this application (if none, type or write none):

August 23, 2000

④ I hereby appoint the following attorneys, with full power of substitution and revocation, to prosecute this application and to transact all business in the United States Patent and Trademark Office connected therewith and request that all correspondence and telephone calls in respect to this application be directed to: BREZINA & EHRLICH, 47 West Polk St., Suite 333, Chicago, Illinois 60605-2092, Telephone No. (312) 408-0077. John C. Brezina, Pat. Reg. No. 18,236; Ira Schultz, Pat. Reg. No. 28,666; Paul Y. Feng, Pat. Reg. No. 33,689; Howard B. Rockman, Pat. Reg. No. 22,190; et al.

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application for any patent issued thereon.

Full name of the first (joint
if other inventors identified)
and (sole if only inventor
identified) inventor:

Reinhold Reiling

Typed or Printed Name

Inventor's signature:

Reinhold Reiling

Date:

Residence and Post Office
Address:

Remchinger Strasse 4

D-75203 Königsbach-Stein

Germany

DEK

Citizenship (Country):

Germany

DECLARATION AND POWER OF ATTORNEY

-continued-

2-00

Full name of the second
joint inventor:

Karl Reiling

Typed or Printed Name

Inventor's signature:

Karl Reiling

Date:

Residence and Post Office
Address:

Remchinger Strasse 4

D-75203 Königsbach-Stein

Germany

DEK

Citizenship (Country):

Germany

Full name of the third
joint inventor:

Typed or Printed Name

Inventor's signature:

Date:

Residence and Post Office
Address:

Citizenship (Country):

Address for Correspondence:

BREZINA & EHRLICH
47 West Polk Street
Suite 333
Chicago, Illinois 60605-2092
(312) 408-0077